

A photograph of several large, rusted industrial pipes stacked together. The pipes are dark brown and show significant corrosion. The background is dark, making the pipes stand out.

CO₂ STORAGE IN DEPLETED GAS FIELDS

Filip Neele, Stefan Belfroid, Aris Twerda




ECN › TNO innovation
for life

STORAGE IN DEPLETED GAS FIELDS

- › First choice for CO₂ storage in The Netherlands
 - › ~ 1.5 Gt capacity in ~100 offshore fields
 - › Re-use of pipelines, platforms, wells

- › Competition with other uses for offshore area
 - › Wind farms
 - › Energy storage or conversion

- › First gas fields (cluster) under development for CCS
 - › Porthos consortium (Rotterdam)



North Sea Energy
www.north-sea-energy.eu

ALIGN - CCUS DEVELOPING CAPACITY

- › Abundant storage capacity, but how to develop it?
 - › Potential timeline of field development
 - › Ranking of options – unit storage cost, location, capacity, etc.

DGF: depleted gas field

DSF: deep saline formation

Several clusters
in central DCS

K14-K15 cluster
Several fields

Q1 cluster
DGF, DSF

Re-use oil
pipeline?
(~75 km)

Second choice?
(~20 km)

P15 cluster
35 Mt


First choice
(~25 km dist.)

P18 cluster
35 Mt




ation
e

T&S SYSTEM



RE-USING DEPLETED FIELDS (AND THE WELLS)

- › Safe storage
 - › Well integrity maintained during operations
 - › Injection on – off: temperature cycling in well
 - › **Wellhead: $T > -10\text{ °C}$** (material constraint)
 - › Reservoir and cap rock integrity preserved
 - › Large contrast temperature CO_2 - reservoir
- › Maintain operability of reservoir
 - › Avoid salt deposition and hydrate formation
 - › Hydrates: **bottomhole $T > 15\text{ °C}$**
- › Flow rates through well: limits due to erosion, vibration



Need water...

EXAMPLE: LIQUID, COLD CO₂ CONDITIONS ALONG WELL


- › TVD ~ 3.5 km (deviated well)
- › At wellhead:
 - › Massflow: 10 - 170 kg/s
 - › Pipeline pressure 100 bar
 - › Wellhead temperature: 10 °C
- › Near bottom of well:
 - › Reservoir pressure: 20 bar
 - › Reservoir temperature: 120 °C

Results depend on well completion, reservoir properties, etc.: system design to take the flow phenomena into account

Minimum safe injection rate
80 kg/s (~2.5 Mtpa)
(only for this particular set-up!)



-10 °C
(wellhead)

15 °C (bottom hole)




DYNAMIC OPERATIONS – SHUTIN

- › Shutin
 - › Reservoir pressure 20 bar
 - › Initial mass flow rate 30 kg/s
 - › Well shut in
- › During shutin
 - › Wellhead pressure decreases
 - › Liquid is formed
 - › Conditions shift to phase line
 - › Results in temporary low temperatures
- › Requires detailed heat transfer calculations including heat capacity
 - › Tubing temperatures
 - › Annulus temperatures
 - › Cement bonding



Total time:
90 minutes



CONFORMANCE MONITORING

- › Define site conformance indicators
 - › Pressure, temperature in places in system

- › Compare measured and observed field performance indicators
 - › Measured: noise
 - › Modelled: uncertainties, model limitations

- › What is magnitude of signal in monitoring data from risks that *do* occur, compared to noise and uncertainties?


Regulations in place, but not tested yet

EU Storage Directive & ETS: emphasis on monitoring, measuring and verification

How well can we assess conformance?

EXAMPLE: BHP BASED MONITORING

Correct assessment depends on (a.o.):
 Uncertainties in *a priori* model, variations in CO₂ quality, noise in monitoring data



False negatives, false positives

Improve: decrease uncertainties, add other monitoring techniques

CONCLUSIONS

- › Depleted fields: blessing in disguise?
 - › Abundance of data from production period
 - › Well-defined storage capacity
 - › Pipelines, platforms and wells to be re-used

- › Low pressure represents challenge – injection project becomes temperature management project
- › For NL fields: size (capacity) of fields requires *many* fields to be developed

Acknowledgements

ACT ALIGN CCUS Project No 271501

This project has received funding from RVO (NL), FZJ/PtJ (DE), Gassnova (NO), UEFISCDI (RO), BEIS (UK) and is cofunded by the European Commission under the Horizon 2020 programme ACT, Grant Agreement No 691712

www.alignccus.eu



This work has been produced with support from the ERA-NET ACT Pre-ACT project (Project No. 271497) funded by RCN (Norway), Gassnova (Norway), BEIS (UK), RVO (Netherlands), and BMWi (Germany) and co-funded by the European Commission under the Horizon 2020 programme, ACT Grant Agreement No 691712. We also acknowledge the following industry partners for their contributions: Total, Equinor, Shell, TAQA.



› **THANK YOU FOR YOUR
ATTENTION**

TNO.NL/ECNPARTOFTNO



ECN

› **TNO**

innovation
for life